

DS-1309WB (18V)



Features

- Drive 6-lamps
- Nominal current 7.0 mArms for each lamp
- 16.2 to 19.8V input voltage range
- Accurate and stable output current regulation
- Voltage dimming control
; no influence to power ripple
- Protection against lamp open or failure
- Long lamp life with soft start
- High efficiency
- Low EMI and spurious noise

Applications

- 17~20.1" Desktop LCD monitor
- Industrial LCD panel

Electrical characteristics

Parameter	Symbol	Conditions*	Specification*			Unit
			Min	Typ	Max	
Input supply voltage	V_{IN}		16.2	18.0	19.8	V
Input current	I_{IN}	$V_{IN}=18V, V_{BRT}=0V$	1.3	1.8	2.3	A
Full bright lamp current	$I_{O(MAX)}$	$V_{IN}=18V, V_{BRT}=0V$	6.0	7.0	8.0	mArms
Minimum lamp current	$I_{O(MIN)}$	$V_{IN}=18V, V_{BRT}=5.0V$	2.0	3.0	4.0	mArms
Operating frequency	F_O	$V_{IN}=18V, V_{BRT}=0V$	43	48	53	KHz
Open lamp output voltage	V_O	1 or more lamp open	-	-	0	Vrms
Dimming ratio		$V_{IN}=18V, V_{BRT}=0$ to 5.0V		2 : 1		
Sleep current	I_{IN}	$V_{IN}=18V, V_{SLEEP}=0V$			10	mA
Efficiency		$V_{IN}=18V, V_{BRT}=0V$	80	88		%
Striking voltage	V_s	$V_{IN}=18V, V_{BRT}=0V$		1300		Vrms

* At the reference 20.1"LCD-Module(LM201U03) of LG-Philips

DS-Plus Inc./ ()

Room 403, Ssangyong IT twin tower-1, 442-17 Sangdaewon-dong, Jungwon-gu, Seongnam-city 462-807, Korea
Tel : 82-31-608-7100~3, Fax : 82-31-608-7104

Absolute maximum ratings

DS-1309WB (18V)

Input supply voltage (V_{IN})	-----	-0.3V to 19.8V
Output voltage, no load	-----	Internally limited to zero volt
Output current (I_O)	-----	9.0mA rms
Output power (per lamp)	-----	8.0W
Sleep & Bright adjust signal voltage (V_{SLEEP} , V_{BRT})	----	-0.3V to V_{IN}
Ambient operating temperature	-----	0 °C to 50 °C
Storage temperature range	-----	-30 °C to 80 °C
Operating & storage humidity	-----	10 % to 85 %

Recommended operating conditions (R.C.)


Parameter	Symbol	Recommendation			Units
		Min	R.C.	Max	
Input supply voltage	V_{IN}	16.2	18.0	19.8	V
Full bright lamp current	$I_{O(MAX)}$	6.5	7.0	7.5	mA rms
Brightness control voltage range	V_{BRT}	0		5.0	V
Lamp on/off control voltage	V_{SLEEP}	3.0	5.0	7.0	V
Lamp operating voltage(reference)	V_O		850		V rms
Operating ambient temperature range	T_A	0		50	°C

Connector and functional pin description

- CN1 Connector : 12505WR - 12A00(YEONHO or Equivalent)
 - CN1 - 1,2,3 V_{IN} (DC Input ; 18.0V)
 - CN1 - 4,5,7,8,10,12 G_{ND} (Power supply return)
 - CN1 - 9 V_{SLEEP} (Lamp On/Off control ; Off at Low, On at High)
 - CN1 - 11 V_{BRT} (Bright adjust ; 0 to 5.0V)
 - CN1 - 6 N.C
- CN2,3 Connector : 20015WR - 09A00(YEONHO or Equivalent)
 - CN2,3 - 1,2 High voltage
 - CN2,3 - 3,4 Lamp current return
- CN4,5 Connector : 35001WR - 02A00(YEONHO or Equivalent)
 - CN4,5 - 1 High voltage
 - CN4,5 - 2 Lamp current return

Tolerance : ± 0.5
Unit : mm

Mechanical dimensions



Notice : The specification is subject to change without notice